


2

1


.135 [3.4]

**ORDER OF ASSEMBLY**

CAP



TOP FERRULE

BOTTOM  
FERRULETHREADED  
BODY

5/16-20

1.4 [36.6]

1/4 x 18 NPT

.50 [12.7]

**NOTES**

- 1.) MATERIAL: 316 STAINLESS STEEL
- 2.) NUMBER OF FERRULES: 2 (DOUBLE TYPE)
- 3.) PRESSURE RATING: 6600 PSI (454 bar)

**GENERAL TOLERANCES  
DIMENSIONS ARE IN INCHES**

X.XX ±0.01      X.XXX ±0.005  
 ANGULAR ±0.5°  
 BREAK SHARP EDGES & CORNERS 0.010  
 CHAMFER FIRST THREAD 0.010 X 45°

[      ] DIMENSIONS ARE IN MILLIMETERS

DRAWN:	J. Nielson	11/10/2017
CHECKED:	N. Murphy	11/10/2017



THIS DOCUMENT CONTAINS  
 PROPRIETARY  
 INFORMATION AND IS  
 SOLELY FOR THE  
 EXCLUSIVE USE OF THE  
 ORIGINAL ADDRESSEE. IT IS  
 NOT TO BE REPRODUCED,  
 DISTRIBUTED OR DIVULGED  
 IN WHOLE OR IN PART TO  
 ANY OTHER FIRM OR  
 INDIVIDUAL BY ANY  
 MANNER WITHOUT PRIOR  
 WRITTEN PERMISSION  
 FROM: "THE SENSOR  
 CONNECTION LLC."

**Harold G. Schaevitz Industries LLC**

Bloomfield Hills, Michigan  
[www.thesensorconnection.com](http://www.thesensorconnection.com)

**TITLE: CF-0125-14-NPT**

SIZE A	DWG Number 2017-052	REV
-----------	------------------------	-----

SCALE: 1:1	APPROVED: N. Murphy	DATE: 11/10/2017	Sheet: 1 of 1
------------	---------------------	------------------	---------------